



DV652IR

Antivandal Dome Camera with IR

- 1/3 " Sony EXVIEW CCD II Advance Technology
- 650TVL Extremely Resolution
- Built in Removable IR Cut Filter
- Mist-Resistant/IP Cut Filter
- LED Constant Current Control

| Specification | DV652IR |
|-----------------------|-----------------------------------------------|
| Image Sensor: | 1/3 " Sony EXVIEW CCD II |
| Video Format | PAL/NTSC |
| Number of Pixel | PAL: 1020(H) x 596(V) / NTSC: 976(H) x 494(V) |
| Minimum Illumination | 0 Lux. While IR-LED on |
| S/N Radiation | More than 52dB |
| Horizontal Resolution | 650TVL |
| Vertical Resolution | 600TVL/700TVL(B/W) |
| Day/Night Switchable | OSD MENU/Default |
| IRC | Built-in(Color to Mono,.0.5-1.0Lux) |
| IR Visible | 15-25m (lens size) |
| Effective Visible | 8-15m (lens size) |
| IR LEDs | (ø5)36pcs/850nm |
| Electronic Shutter | 1/50~1/100,000 Sec (PAL), 1/60~1/100,000Sec |
| White Balance | OSD MENU/Default |
| DNR | OSD MENU/Default |
| WDR | OSD MENU/Default |
| Motion Detection | OSD MENU/Default |
| Privacy Mask | OSD MENU/Default |
| Gamma | OSD MENU/Default |
| Video Output | BNC 1.0Vp-p 75 Ohm |
| Lens | 2.8-12mm Varifocal Auto IRIS |
| Power Supply | DC12V/1A(MAX) |
| Operation Condition | -40°C~70°C,RH90% (MAX) |
| Material of Body | Aluminum Alloy |
| Water Proof Rated | IP66 |
| Net Weight | 2700g |
| Gross Weight | 3000g |
| Product Dimension | 150x99.5mm(L x W x H) |
| Production Dimension | 190x170x170mm(L x W x H) |

Accessories



DVC500 Bracket

Dimension

